THE LEGEND LIVES ON

TEN-TEC ARGONAUT VI QRP WITH AUTHORITY

PRELIMINARY SPECIFICATIONS

History lives on from the designer who brought you the original Argonaut Series



LOW POWER + TEN-TEC PERFORMANCE = FUN

- Modes: CW, LSB, USB, AM
- Receiver Type: Double Conversion, ASR
- RIT: +/- 8.2kHz
- CW Keyer built in: Curtis Mode B, 5-50wpm
- Typical receiver sensitivity: < 1 uv
- DSP Selectivity: 100 built in DSP filters from 100Hz.
- · Dynamic Range: 91db
- Display: Multicolor back lit LCD
- Rf Output power: 1 to 10 watts

- Transmitter Duty cycle: 100% for up to 10 minutes
- Frequency Coverage: 160 through 10 meters with the exception of 60 and 12 meters.
- Power Requirements: 9.5-14 Volts DC (550ma on receive, 3 amps at 10 watt TX)
- VFO: Two independent "VFOs" for single or split operation
- Speed Sensitive VFO tuning rate
- Frequency Stability: +/- .5ppm
- Memories: 100

Find out more

www.tentec.com

BUY FACTORY DIRECT





1185 Dolly Parton Pkwy., Sevierville, TN 37862 • Sales (800) 833-7373 • sales@tentec.com • Office (865) 453-7172 • Fax (865) 428-4483 Service: (865) 428-0364 • service@tentec.com • M-F 8 AM - 5 PM (Eastern Time). We accept Visa, MC, American Express and Discover.